








	Image	Brand	Model	Comment	Main Interfaces	Drop Rating	IP	Print Speed (Max)	Weight	Dimensions	Roll Diameter	Emulation	Gap/Black Mark	Battery
2" Print Width		Bixolon	SPP-R210		BT/Wi-Fi	1.2m	IP54 (with case)	90mm	232g	79.0 x 116.0 x 36.5 mm	30mm	ESC POS	Receipt Only or linerless/continuous	1200mAh
		Bixolon	SPP-R200III		BT/Wi-Fi	2.1m	IP43 / IP54 with case	100mm	228g	79.5 x 126.7 x 43.6 mm	40mm	ESC POS	Receipt & Most Label	1200mAh
		TSC	Alpha 2R		BT/Wi-Fi	1.5m/2m with case	IP54 (with case)	102mm	350g	89.3 x 134.5 x 56.5 mm	50mm	TSPL/EPL/ZPL/ESC POS/CPCL	Receipt & Most Label	1620mAh
3" Print Width		Bixolon	SPP-R310		BT/Wi-Fi	1.8m	IP54	100mm	385g	105.0 x 126.0 x 58.0 mm	50mm	ESC POS	Gap and black mark optional	2600mAh
		TSC	Alpha 3R		BT/Wi-Fi	1.5m	IP54 (with case)	102mm	550g	116 x 148 x 70 mm	55mm to 57mm	TSPL/EPL/ZPL/ESC POS/CPCL	Black mark	2500mAh
4" Print Width		Bixolon	SPP-R410		BT/Wi-Fi	1.8m	IP54	90mm	530g	143 x 138 x 66 mm	57mm	ESC POS	Gap and black mark optional	2600mAh
		TSC	Alpha 4L	Optional LCD	BT/Wi-Fi	1.5m (1.8m with case)	IP54 (with case)	102mm	1.1kg	160 x 191.6 x 79 mm	67mm	TSPL/EPL/ZPL/ESC POS/CPCL	Gap and black mark	5800mAh