

UROVO

Enterprise Mobile Computer

DT50P

- 5dB high sensitivity RFID antenna expands reading coverage. Batch reading limitation now is 15M.
- With Self Jammer Cancellation (SJC) and high density recognition technology , easily find all tags in metal or huge volume environment.
- Ergonomic pistol grip design, minimized fatigue and delivered high efficiency during long hours of operation.
- Hi-tech thermal material with optimized fluid mechanics algorithm, expressed cool, economic, long-lasting performance, supporting every challenging task.
- Embedded market leading scan engine, auto-corrects damaged/ distorted barcode.



IP67
sealing




UHF
RFID



5.7" Giant
touch screen



Octa-core high
processor



1.2m drop
resistance



UEE UROVO
Enterprise Enabler



DT50P Enterprise Mobile Computer


Specifications


UROVO


 **Processor**
Octa-core 2.0GHz
Octa-core 2.45GHz (optional)


 **O.S.**
Android 11.0


 **Memory**
RAM: 4GB ROM: 64GB
Micro-SD card, Up to 256 GB

 **Display**
5.7 inch display,
720*1440, 1080*2160 (optional)

 **Touch Screen**
Ultra sensitive capacitive touch panel
Support multi-touch
Works with gloves and wet fingers

 **Dimensions**
Dimensions: 143.3*169*90.5mm
Weight: 678g


 **Scanning**
Professional scan engine;
Support international
standard 1D/2D barcode;
Support barcode displayed
on screen and colored barcode;


 **RFID(UHF)**
RFID tags reading,
up to 15m


 **Audio**
Dual-Microphone
(noise cancellation);
Speaker (1.5W);
Receiver

 **Main battery**
Capacity: 3.85V/9000mAh

 **Camera**
Front 5MP
Top 13MP with flash


 **Buttons**
PWR button
Vol+/- button
scan button*2
custom button

 **Slots**
Micro SD/TFx1
Nano- SIMx2

 **WWAN**
4G, 3G, 2G
Bluetooth: BT 5.0+BR/EDR+BLE
WIFI: 2.4G/5G, IEEE 802.11a/b/
g/n/ac/d/e/h/i/k/r/v/w
WIFI 6 (optional)

 **Positioning**
GPS
A-GPS
BeiDou
GLONASS
Galileo

 **Sealing**
IP67
1.2m drop resistance

 **Environment**
Operating Temp.: -20 ~ +60°C
Storage Temp.: -40 ~ +70°C
Humidity: 5%RH~95%RH ((No condensation)
ESD: +/-15kv Air; +/-8kv contact

Urovo Technology Co., Ltd.

• Tel: 86 755-22673926 • Website: en.urovo.com • E-mail: urovo@urovo.com
• Address: Room 613,6/F.,Asia Trade Centre,79 Lei Muk Road,Kwai Chung,N.T.,Hong Kong

* This page is subject to change
without prior notice