

Upgrade your experience with a combination of speed, convenience and portability

- Versatile mobile terminal powered by Android 13 for all mobile business needs.
- Supported by LANDI's asset management platform, LANDI Connect, to meet the
 evolving demands of today's digital world.
- Pocket-size design, enabling high-level productivity and connectivity on the go.



- Expansive 6.517" touch screen and ergonomic interface
- Powerful processor for smooth operation (Qualcomm Quad-core, 2.0GHz)
- Quick-swap battery on duty(3500mAh/7.7V)
- Advanced connectivity for high-mobility(2G/3G/4G, WiFi, GPS, Bluetooth 5.0, and optional eSIM)
- 5MP rear camera for convenient QR code reading Optional front camera



SPECIFICATIONS

Processor	Qualcomm Quad-core, 2.0GHz	Positioning	GPS, GLONASS, BEIDOU
os	Android 13 (GMS Certified)	Camera	Front camera: optional, 2M pixels, fixed focus camera, for code scanning Rear camera: 5M pixels, autofocus and flashlight
Memory	3GB RAM+32GB FLASH 4GB RAM+64GB FLASH (Optional) 2GB RAM + 16GB FLASH (Optional, No GMS) Micro SD Card (Up to 2TB)		
		NFC (Optional)	Android NFC, ISO/IEC 14443, ISO15693 compliant, support Type A/B, Mifare, Felica
Display & Touchscreen	6.517", IPS, 720x1600 HD capacitive multi-touch		
Scanner	· Option 1: None · Option 2: LANDI Scan Engine · Option 3: Honeywell Scan Engine	SIM/SAM Slots	· 2 SIM + 2 SAM · eSIM (Optional)
		Connection	· 1 USB Type-C · 2 PIN Pogo Pin
Buttons	1 power key (Right side) 2 scan code keys are located on each side (Optional) 2 volume keys (Left side)		
		PSU	5V/2A
		Battery	3500mAh/7.2V, removable
Audio	Speaker: 1W 90dB@0.1m Headset: USB Type-C MIC: Dual MIC	Size	L-17cm W-8cm H-2cm 6.69" x 3.15" x 0.79"
Connectivity	Cellular: 4G fallback 3G and GPRS, Global band Wi-Fi: IEEE 802.11 a/b/g/n/ac 2.4G and 5G Bluetooth: Bluetooth 5.0, support BLE	Accessories (Optional)	Terminal charging base;Battery charger (Support 4 batteries)Hand strap
Protection	1.2m drop tested *Data from LANDI lab	Environment	Operating temperature: -10°C to +50°C Storage temperature: -20°C to +70°C Operating humidity: 10% to 90% noncondensing
Sensor	· G-sensor, support screen rotation automatic · Light Sensor		
		Certifications	CE/CB/FCC/IC/RoHS/WEEE/GMS

*When MicroSD card is inserted. Card slot is 1 SIM + 1 MicroSD + 2 SAM.



